RUBBER PROFILE SAL SBR/EPDM



APPLICATION

Sound absorption lining for steel straps and pipe clamps (also according to DIN 4109).

Application up to +110°C.

TECHNICAL DATA

Material: SBR/EPDM, black.

Hardness: 45+/-5° Shore

Temperature range: -50°C up to +110°C

Breaking elongation: 560 %

Tear strength: 500 N/cm2

Impact absorption: 39 %

Fire resistance: Material category B2 (DIN 4102), non-dripping.

Sound absorption: up to18 dB(A) (from height 4.5 mm on)

Surface resistance: 2 x 1013 Ohm

Volume resistance: 2 x 1013 Ohm

Fully resistant to: Diluted acids, lyes, alkaline solutions, water, aqueous solutions up to 70°C; No absorption of moisture

Partially resistant to: Grease, mineral oil, animal or vegetable fats, ester and ketones.

Not resistant to: Hot oils, fuels, aliphatic and aromatic hydrocarbons and chloric gas.

Durability: Weatherproof, ageing and ozone-resistant, DIN 53508 and 53509 tested.

Type	Steel strap [mm]	H [mm]	Number ofribs	Weight[kg/m]	Quantityroll[m]
STD 1	25 x 3.0	4.5	4	0.22	30
STD 2	30 x 3.0	4.0	4	0.23	30
STD 3	40 x 4.0	6.0	5	0.37	30
STD 4	50 x 5.0	7.0	5	0.54	30
STD 5	70 x 6.0	7.0	7	0.65	30

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
146502	STD1 h=4,5 mm collare 25×3,0	0.22	30
146511	STD2 h=4,0 mm collare 30×3,0	0.23	30
146520	STD3 h=6,0 mm collare 40×4,0	0.37	30
146539	STD4 h=7,0 mm collare 50×5,0	0.54	30
146548	STD5 h=7,0 mm collare 70×6,0	0.55	30