STABIL C LK





APPLICATION

Used for industrial installations in suspended pipe supports, in accordance with DIN 3567 type C. The cross-section of the metal clamp complies with VdS standards.

TECHNICAL DATA

Material: steel St 37, electro-galvanized.
Bolts and hex nuts M10, steel grade 8.8, pre-assembled.

DN	Ø [mm]	Clamp sectionb x s [mm]	L [mm]	a [mm]	L1 [mm]	L2 [mm]	L3 [mm]	Max safe load [kN]
15	22	25 x 3	81	7	22	17	25	10
20	27	25 x 3	84	7	22	17	25	10
25	34	25 x 3	87	7	22	17	25	10
32	43	25 x 3	92	7	22	17	25	10
40	50	40 x 3	95	7	22	17	25	15
50	62	40 x 3	111	7	22	17	25	15
65	78	40 x 3	134	7	22	17	25	15
80	91	40 x 3	156	7	22	17	30	15
100	116	40 x 4	188	7	22	17	30	15
125	148	40 x 4	204	7	22	17	30	15
150	173	40 x 4	217	7	22	17	30	15
200	225	40 x 4	243	7	22	17	30	15

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

DN	Ø Pipe outer diameter [mm]	Weight [kg]
15	21,3	0,27
20	26,9	0,3
25	33,7	0,31
32	42,4	0,3
40	48,3	0,44
50	60,3	0,51
65	76,1	0,56
80	88,9	0,65
100	114,3	0,78
125	139,7	1,08
150	168,3	1,18
200	219,1	1,39

Codice	Nome	Peso	Numero di pezzi
113103		0.45	25
113104		0.48	25
113105		0.54	25
113106		0.57	25
113107		0.58	25
113108		0.98	10
113109		1.17	10
113110		1.24	10
113111		1.83	10
113112		1.98	10
113113		2.16	1
113114		3.74	1
113115		5.24	1
113116		5.84	1
113018	PIASTRA HPA M12-2	0.2	10
113019	PIASTRA HPA M16-2	0.16	10
113919	SUPPORTO REGOLABILE LKV M10	0.32	10

Codice	Nome	Peso	Numero di pezzi
113920	SUPPORTO REGOLABILE LKV M12	0.7	10
113921	SUPPORTO REGOLABILE LKV M16	1.1	10

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com