
PROFILATI 41/82



DESCRIPTION

Double channels (41 base system) are connected by clinching. Supplied in standard lengths of 3 m or 6 m.

Channels with a length of 2 m or cut-to-size versions are available upon request.

INSTALLATION

If required, double channels can be assembled directly on site by joining two single channels:

with slot type 2: use M8 × 16 bolts
with slot types 3 and 4: use KL 1 coupling clamp

Attention: the channels must be connected together at intervals of 250 mm, including the end sections.

All channels with 41 base are internally serrated and compatible with the components of our system range, such as: HZ hammer-head nuts, WBD base plates, TCS 1 beam clamps, Pressix 41, etc.

TECHNICAL DATA

Material: steel grade 1.0350 (ST 37.2)
Surface finish: Sendzimir hot-dip galvanization according to DIN EN 10327

Load data for channels available in the relevant technical documentation.

Codice	Nome	Peso	Numero di pezzi
193798C	PROFILATO 41/82/2,50 - 6 MT	4.13	240

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com