

GUARNIZIONI ADATTATORE A FLANGIA 7012



High-flexibility asbestos-free gasket material based on organic and synthetic fibers bonded with NBR/SBR rubber.

Manufactured in Europe.

Standard color: Light green

Graphite coating: on one side

APPLICATION

Suitable for use with water, potable water, and compressed air.

TECHNICAL DATA

Thickness range: from 0.50 mm to 5.00 mm

Dimensions: standard sheets 1500 x 1500 mm, on request 1500 x 3000 mm

Thickness: 2.0 mm

Density (DIN 28090-2): 1.9 g/cm³

Tensile strength (ASTM F 152): > 10 MPa

Compressibility (ASTM F 36-J): 10%

Recovery (ASTM F 36-J): min. 50%

Residual stress (DIN 52913): 20 MPa (175°C)

Gas permeability (DIN 3535/6): 0.10 mg/(s·m)

Ignition loss (ASTM F 495): max. 40%

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

IRM 903 oil (ASTM F 146): +15%
(5 h at 150°C – thickness variation)

ASTM B fuel (ASTM F 146): +15%
(5 h at 23°C – thickness variation)

Maximum temperature: 210 °C

Minimum temperature: -40 °C

Maximum pressure: 40 bar

Continuous operating temperature: 140 °C

Maximum temperature with steam: 110 °C

CERTIFICATIONS

DIN 28 091-2: FA-Z-12-0

ASTM F 104: F712 120 M4

Drinking water approval KTW-TZW: No. KA 242/09 (see downloadable Technical Documentation)

Drinking water approval WRAS: No. 1605525 (see downloadable Technical Documentation)

Codice	Nome	Peso	Numero di pezzi
7012060G	2"	0.01	1
7012076G	2 1/2"	0.01	1
7012089G	3"	0.01	1
7012114G	4"	0.01	1
7012139G	5"	0.01	1
7012168G	6"	0.01	1
7012219G	8"	0.01	1
7012273G	10"	0.01	1
7012324G	12"	0.01	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com