




PIPE SHOE LC-HV



APPLICATION

Pipe Shoe - Double Clamp

For pipes on suitable surfaces. Height-adjustable in steps of 2.5 mm. When resting on steel beams, a minimum flange width of 80 mm is recommended.

SCOPE OF DELIVERY

Upper and lower part are bolted together allowing height adjustment. The slide plate is fixed to the lower part.

TECHNICAL DATA

Type	Height Has delivered [mm]	Height Hrange [mm]
LC - HV 90	90	88.5 ... 113.5
LC - HV 150	150	116 ... 168.5
LC - HV 200	200	171 ... 223.5

Tightening torque screw connections:

Clamping bolts	tightening torque[Nm]	height adjustment	tightening torque[Nm]
DN 15 - 40	40	bolts in the bar	80
DN 50 - 200	50	bolts in the bar	80
DN 250 - 300	60	bolts in the bar	80

Dimensions:

- Metal plate: L = 250 mm x B = 100 mm
- Slide plate incl.: L = 256 mm x B = 105 mm

Material:

- Metal parts: Steel, HCP
- Bolts, nuts: Steel, HCP
- Slide plate: Polyamide 6.0, glass fibre reinforced, black

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Media temperature t_f : -20 to +300° C (if $t_f > 270^\circ\text{C}$, remove slide plate).

For dimensions and load charts, please refer to the following pages:

MEASUREMENTS

WORKING LOADS FOR SLIDING SUPPORTS LC - HV

APPROVALS

Certification of quality TUV-Rheinland nr.102793.



Codice	Nome	Peso	Numero di pezzi
110062	LC - HV 90 DN 25	3.6	-
110064	LC - HV 90 DN 40	3.7	-
110065	LC - HV 90 DN 50	4.1	-
110066	LC - HV 90 DN 65	4.3	-
112392	LC - HV 90 DN 15	3.48	-
112393	LC - HV 90 DN 20	3.52	-
110063	LC - HV 90 DN 32	3.7	-
110067	LC - HV 90 DN 80	4.4	-
110068	LC - HV 90 DN 100	5.1	-
110069	LC - HV 90 DN 125	5.4	-
110070	LC - HV 90 DN 150	7.4	-
110071	LC - HV 90 DN 200	8.3	-
110072	LC - HV 90 DN 250	11.1	-
110073	LC - HV 90 DN 300	12	-
112394	LC - HV 150 DN 15	3.98	-
112395	LC - HV 150 DN 20	4.04	-
110074	LC - HV 150 DN 25	4	-
110075	LC - HV 150 DN 32	4.1	-
110076	LC - HV 150 DN 40	4.2	-
110077	LC - HV 150 DN 50	4.6	-
110078	LC - HV 150 DN 65	4.8	-
110079	LC - HV 150 DN 80	4.9	-
110080	LC - HV 150 DN 100	5.5	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
110081	LC - HV 150 DN 125	5.8	-
110082	LC - HV 150 DN 150	7.8	-
110083	LC - HV 150 DN 200	8.8	-
110084	LC - HV 150 DN 250	11.6	-
110085	LC - HV 150 DN 300	12.6	-
112396	LC - HV 200 DN 15	4.48	-
112397	LC - HV 200 DN 20	4.5	-
110086	LC - HV 200 DN 25	4.6	-
110087	LC - HV 200 DN 32	4.9	-
110088	LC - HV 200 DN 40	4.9	-
110089	LC - HV 200 DN 50	5.2	-
110090	LC - HV 200 DN 65	5.3	-
110091	LC - HV 200 DN 80	5.4	-
110092	LC - HV 200 DN 100	6.1	-
110093	LC - HV 200 DN 125	6.2	-
110094	LC - HV 200 DN 150	8.4	-
110095	LC - HV 200 DN 200	9.5	-
110096	LC - HV 200 DN 250	12	-
110097	LC - HV 200 DN 300	13	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com