U BOLT RUB SS



APPLICATION

For pipeline systems in industrial and residential buildings and Sprinkler installations meeting the VdS and FM standards.

For horizontal and vertical pipelines, the U-Bolts are applied as Fixed Points and as Guiding Supports.

SCOPE OF DELIVERY

Four hexagon nuts included in loose form.

INSTALLATION

When used as Guided Support, nuts have to be arranged and fixed on both sides, at the top and at the bottom of the profile. Thereby the pipe should remain flexible. When used as Fixed Point the admissible loads of the connecting elements shouldn't exceed the bending loads of the U-bolt.

TECHNICAL DATA

Material: Stainless steel A4.

Specification: Similar to DIN 3570 standard.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	NB	B [mm]	L1 [mm]	L2 [mm]	Thread
21.3	1/2"	30	45	30	M 8
26.9	3/4"	35	60	40	M 8
33.7	1"	42	67	40	M 8
42.4	1 1/4"	51	76	40	M 8
48.3	1 1/2"	57	82	40	M 8
60.3	2"	71	95	45	M 10
76.1	2 1/2"	87	111	45	M 10
88.9	3"	100	123	45	M 10
114.3	4"	126	157	55	M 12
108		121	151	55	M 12
139.7	5"	152	180	55	M 12
133		146	172	55	M 12
159		172	197	55	M 12
168.3	6"	180	207	55	M 12
219.1	8"	233	267	55	M 12
274.0	10"	302	314	70	M 20

APPROVALS

Size NB 8" with M12 thread obtained a separate VdS Approval: No. G4810047.

Codice	Nome	Peso	Numero di pezzi
102719	21,3 mm ½''	0.05	50
102728	26,9 mm ¾''	0.07	50
102737	33,7 mm 1''	0.07	50
102746	42,4 mm 1 ¼''	0.08	50
102889	48,3 mm 1 ½''	0.08	50
102898	60,3 mm 2''	0.16	50
102904	76,1 mm 2 ½''	0.18	50
102913	88,9 mm 3''	0.2	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
102922	108,0 mm	0.34	50
102694	114,3 mm 4''	0.35	25
102685	133,0 mm	0.39	25
102931	139,7 mm 5''	0.39	25
102940	159,0 mm	0.42	25
102700	168,3 mm 6''	0.44	10
102959	219,1 mm 8''	0.55	10
102968	273,0 mm 10''	1.88	10