
STABIL D-M 16





APPLICATION

For installation of pipes required for M&E services and in plant construction.

SCOPE OF DELIVERY

With welded M16 nut; clamping bolts and nuts included in loose form.

Other welded nuts (e.g. M20) or inch sockets available on request.

TECHNICAL DATA

Material: Steel, electro-galvanised.

Size range[mm]	Clampingbolts	B [mm]	L [mm]	Material [mm]	Connection
218 - 227	M12 x 40	301	275	40 x 4	M12 x 40
271 - 277	M12 x 40	351	325	40 x 4	M12 x 40
316 - 324	M16 x 60	440	390	50 x 5	M16 x 60
348 - 356	M16 x 60	471	421	50 x 5	M16 x 60
360 - 368	M16 x 60	483	431	50 x 5	M16 x 60
399 - 407	M16 x 60	520	470	50 x 5	M16 x 60
411 - 419	M16 x 60	532	482	70 x 6	M16 x 60
500 - 508	M16 x 60	619	569	70 x 6	M16 x 60
513 - 521	M16 x 60	631	581	70 x 6	M16 x 60

APPROVAL

Certificate FM for DN 218-277.

FM APPROVED

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
118772	218 - 227 mm * 8''	1.42	10
118198	271 - 277 mm 10''	1.42	10
103844	316 - 324 mm 12''	2.47	1
103862	348 - 356 mm 14''	2.48	1
103871	360 - 368 mm	2.99	1
103905	399 - 407 mm 16''	2.95	1
103914	411 - 419 mm	5.12	1
103941	500 - 508 mm 20''	6.06	1
103950	513 - 521 mm	6.34	1