DUCTING CLAMP PLU 2G-N WITH LINING



APPLICATION

Two-piece pipe clamp for simple installation of spiral-seam ducts.

Suitable for soundproof installation according to DIN 4109.

SCOPE OF DELIVERY

Clamping bolts are pre-mounted and retained. Pivot screw for safe and simple assembly with quick-set clip, suitable for "single-hand" mounting. Easier handling and better storage possibilities due to optimized packaging.

INSTALLATION

Tighten upper part of the pipe clamp without the interfering lower part.

Hook lower part, provided with a keyhole, into the fixed clamping bolt (see picture).

After inserting the pipe and locating into the pivot screw, the clamping bolt head is located behind the angled profiles; then tighten clamping bolt with max. 2 Nm.

TECHNICAL DATA

Material: Steel, galvanised;

Insulation insert: SBR/EPDM black (see section "RUBBER PROFILE SAL SBR/EPDM" for technical data).

Type	Material[mm]	Perm. load capacity[kN]	Threadconnection
71 - 200	20 x 1.5	0.8	M8/M10
224 - 500	25 x 1.5	1.0	M8/M10

Codice	Nome	Peso	Numero di pezzi
199824	DN 71	0.1	50
199831	DN 80	0.12	50
199848	DN 90	0.12	50
199855	DN 100	0.14	100
199862	DN 112	0.15	100

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
199879	DN 125	0.16	100
199886	DN 140	0.17	70
199893	DN 150	0.19	70
199909	DN 160	0.19	70
199916	DN 180	0.21	50
199923	DN 200	0.23	50
199930	DN 224	0.31	50
199947	DN 250	0.37	40
199954	DN 280	0.36	40
199961	DN 300	0.38	40
199978	DN 315	0.42	40
199985	DN 355	0.46	40
199992	DN 400	0.52	30
199993	DN 450	0.58	20
199994	DN 500	0.64	20