
# SOUND ABSORPTION UNIT SDE



## APPLICATION

Sound absorption element to be used in combination with Sikla Channels 27 in ducting systems (respecting sound proof demands according to DIN 4109).

The geometry of this element reliably secures sound absorption between channel and suspension.

## SCOPE OF DELIVERY

Completely assembled with inserted and retained washer.

## INSTALLATION

Clamp the sound absorption element into the round hole of the channel back and into the channel opening. Thread to be pulled through and contered afterwards.

## TECHNICAL DATA

Material: TPE, black

Temperature range: -50°C to + 110°C

Fire resistance: B2 according to DIN 4102, non-dripping

Hardness: 50°+/-5° Shore

| Type | For channel | Threadconnection | Total-Height [mm] | Heightof collar [mm] |
|---|---|---|---|---|
| 27 | | M8 | 15 | 7 |
| 41 | 41 | M8/M10 | 18 | 10 |

| Codice | Nome | Peso | Numero di pezzi |
|---|---|---|---|
| 197973 | Tipo 27 | 0.01 | 100 |
| 107802 | Tipo 41 | 0.01 | 100 |

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

**info@prosystemitalia.com**
**prosystemitalia.com**