DUCTING CLAMP PLU 2G-N



APPLICATION

Two-piece pipe clamp for simple installation of spiral-seam ducts.

SCOPE OF DELIVERY

Clamping bolts are pre-mounted and retained. Pivot screw for safe and simple assembly with quick-set clip, suitable for "single-hand" mounting. Easier handling and better storage possibilities due to optimized packaging.

INSTALLATION

Tighten upper part of the pipe clamp without the interfering lower part.

Hook the lower part, provided with a keyhole, into the fixed clamping bolt (see picture). After mounting of the pipe and locating into the pivot screw, the clamping bolt is fixed behind the bending; then tighten clamping bolt with max. 2 Nm.

TECHNICAL DATA

Material: Steel, galvanised.

Type	Material[mm]	Perm. load capacity[kN]	Thread connection
71 - 200	20 x 1.5	0.8	M8/M10
224 - 500	25 x 1.5	1.0	M8/M10

Codice	Nome	Peso	Numero di pezzi
199626	DN 71	0.09	50
199633	DN 80	0.1	50
199640	DN 90	0.1	50
199657	DN 100	0.11	100
199664	DN 112	0.12	100
199671	DN 125	0.13	100
199688	DN 140	0.14	80

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
199695	DN 150	0.15	80
199701	DN 160	0.16	80
199718	DN 180	0.17	50
199725	DN 200	0.18	50
199732	DN 224	0.24	50
199749	DN 250	0.25	40
199756	DN 280	0.29	40
199763	DN 300	0.32	40
199770	DN 315	0.32	40
199787	DN 355	0.37	40
199794	DN 400	0.41	30
199800	DN 450	0.43	20
199817	DN 500	0.5	20