T-HEAD BOLT CLICK-EASY



APPLICATION

Suitable for channel with width 30 and 32 mm.

SCOPE OF DELIVERY

Already fitted with washer, hex nut and threaded rod in the different sizes.


TECHNICAL DATA


Material: Steel cold-worked and electro-galvanised.

Max. Working load: 1,8 kN

Max. tightening torque: 10 Nm

Type	Bar lenght [mm]	A [mm]	B [mm]	C [mm]	D x d [mm]
M8 x 30	30	16	30	36 x 13,8	28 x 8,6
M8 x 40	40	26	40	36 x 13,8	28 x 2,6
M8 x 50	50	36	50	36 x 13,8	28 x 2,6
M10 x 30	30	26	40	36 x 13,8	28 x 10,6
M10 x 40	40	26	40	36 x 13,8	28 x 10,6
M10 x 50	50	36	50	36 x 13,8	28 x 10,6





PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
80380	M 10×40 mm	0.05	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com