

BEAM CLIP P



APPLICATION

Universal clamping element for bi-lateral attachment of crossbars for pipe runs, ducts, cable lines and equipment to steel beams.

The maximum clamping range may be extended by up to 10 mm by using spacers. Any thicker spacers should be welded to the crossbar.

INSTALLATION

Determination of the required bolt length L_{min} :

Type	Arrangement A	Arrangement B
P1	$L_{min} = a + b + 37$ [mm]	$L_{min} = b + 40$ [mm]



TECHNICAL DATA

Arrangement A

Arrangement B Pass-through bolt with holding bracket

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Channel nut HZP 1: $L_{min} = a + b + 37$ [mm]P 1: $L_{min} = b$

+ 40 [mm]

Max. working load: 4 kN

Max tightening torque

Bolt: M8 or M10 \pm 10%: 50 Nm

Material: Cast iron or steel.

Tipo	b[mm]	\varnothing D[mm]	L[mm]	B[mm]
P 1	1 - 23	11	50	36



Codice	Nome	Peso	Numero di pezzi
116196	P1 \varnothing 11 mm	0.09	50

PROSYSTEM ITALIA SRLVia Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219info@prosystemitalia.com
prosystemitalia.com