PIERCING TOOL LOT



APPLICATION

For simultaneously punching two holes of Âø 10.5 mm into trapezoidal corrugated roofing of a maximum thickness of 1.2 mm, providing for the subsequent mounting of a Roof Hanger.

The optimised transformation allows already with very less strength a high cutting force at the hole punches. Thus several successively piercings or piercings in thicker sheets are possible without problems.

Further advantages are:

- Continous adjustment of the cutting width for application of various profiles from 40 - 100 mm
- Continous adjustment of the height position for an exact and uniform alignment of the hole positions taken from the lower edge of the trapezoidal corrugated sheet.
- After piercing, ejector springs ensure a safe return stroke of the hole punches.

SCOPE OF DELIVERY

Completely with hole punches.

Hole Punches could be re-ordered or exchanged if required.

TECHNICAL DATA

Total length: 710 mm

Material:

- Holders: Steel tube, lacquered with plastic grip;
- Joint parts; Steel;
- Hole punch: Steel, tempered, ø 10,5 mm;
- Ejector springs: Stainless steel.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
171296	LOT3	2.47	1