Rubber Profile SAL EPDM sk



APPLICATION

Sound absorption lining for steel straps and pipe clamps.

SCOPE OF DELIVERY

In rolls, self-adhesive on one side, coated with peel-off foil on the adhesive side.

TECHNICAL DATA

Sound absorption value: 12 dB(A)

Hardness: 20° Shore

Temperature range: -25°C up to +95°C

Resistent to: Diluted acids,lyes,alkaline solutions, water,aqueous solutions up to 70°C; no absorption of moisture

Not resistant to: Hot oils, fuels, aliphatic and aromatic hydrocarbons and chloric gas.

Codice	Nome	Peso	Numero di pezzi
188075	SK 30×1,0 mm L=20 m	0.05	20
188084	SK 40×1,0 mm L=20 m	0.06	20
188093	SK 50×1,0 mm L=20 m	0.09	20
188102	SK 60×1,0 mm L=20 m	0.11	20
188111	SK 70×1,0 mm L=20 m	0.11	20

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com