
STABIL D SS





APPLICATION

For the installation of pipes required for all M&E services in industrial, residential and public buildings.

SCOPE OF DELIVERY

Two-piece pipe clamp without clamping bolts and nuts.

INSTALLATION

Particularly suitable for two-point mountings.

TECHNICAL DATA

Material: Stainless steel V4A

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Size range[mm]	Max. perm. working load [kN]	MaterialW x th[mm]	Recommendedclamping bolts	B [mm]	L [mm]
18 - 22	5.0	25 x 3	M8 x 25	70	50
24 - 28	5.0	25 x 3	M8 x 25	77	57
30 - 34	5.0	25 x 3	M8 x 25	84	64
35 - 37	5.0	25 x 3	M8 x 25	87	67
40 - 44	5.0	25 x 3	M8 x 25	95	75
47 - 51	5.0	25 x 3	M8 x 25	102	82
54 - 58	5.0	25 x 3	M8 x 25	109	89
59 - 63	5.0	25 x 3	M8 x 25	115	95
67 - 71	5.0	25 x 3	M8 x 25	123	103
74 - 78	6.0	30 x 3	M10 x 30	140	116
81 - 85	6.0	30 x 3	M10 x 30	147	123
86 - 90	6.0	30 x 3	M10 x 30	152	128
94 - 98	6.0	30 x 3	M10 x 30	160	136
102 - 108	6.0	30 x 3	M10 x 30	170	146
108 - 114	6.0	30 x 3	M10 x 30	176	152
116 - 122	6.0	30 x 3	M10 x 30	184	160
133 - 140	6.0	40 x 4	M12 x 35	217	184
145 - 152	6.0	40 x 4	M12 x 35	229	196
159 - 169	6.0	40 x 4	M12 x 35	245	212
170 - 180	6.0	40 x 4	M12 x 35	257	224
198 - 207	6.0	40 x 4	M12 x 35	284	251
210 - 219	6.0	40 x 4	M16 x 50	304	269
222 - 231	6.0	40 x 4	M16 x 50	316	281
247 - 253	6.0	40 x 4	M16 x 50	338	303
271 - 277	6.0	40 x 4	M16 x 50	362	327
312 - 318	6.0	40 x 4	M16 x 50	403	368
322 - 329	6.0	40 x 4	M16 x 50	414	379

Codice	Nome	Peso	Numero di pezzi
172433	18 - 22 mm ½''	0.08	50

Codice	Nome	Peso	Numero di pezzi
172442	24 - 28 mm ¾''	0.09	50
172451	30 - 34 mm 1''	0.1	50
172460	35 - 37 mm	0.11	50
172469	40 - 44 mm 1 ¼''	0.12	50
172478	47 - 51 mm 1 ½''	0.13	50
172487	54 - 58 mm	0.14	50
172496	59 - 63 mm 2''	0.15	50
173081	67 - 71 mm	0.16	50
172505	74 - 78 mm 2 ½''	0.23	25
173090	81 - 85 mm	0.25	25
172514	86 - 90 mm 3''	0.26	25
173099	94 - 98 mm	0.28	25
173144	102 - 108 mm	0.3	25
172523	108 - 114 mm 4''	0.3	25
173108	116 - 122 mm	0.31	25
172532	133 - 140 mm 5''	0.68	10
173117	145 - 152 mm	0.71	10
172541	159 - 169 mm 6''	0.75	10
173126	170 - 180 mm	0.83	10
172550	198 - 207 mm	0.94	10
172559	210 - 219 mm 8''	0.99	10
173135	222 - 231 mm	1.04	10
413725	247 - 253 mm	1.14	10
413734	271 - 277 mm 10''	1.21	10
413743	312 - 318 mm	1.35	10
413752	322 - 329 mm 12''	1.4	10