ERS PIPE CLAMPS



APPLICATION

Two-piece pipe clamp with dual threaded connection M8 and M10 for pipe fastening.
Suitable for fixing pipelines with acoustic insulation requirements in accordance with DIN 4109.

TECHNICAL DATA

Clamping range [mm]	Max. permissible load (tension)	Torque [Nm]	Material b x s [mm]
13–89	0.55 kN	1	20 x 1.0
39–66	0.80 kN	2	20 x 1.2
75–115	0.90 kN	2	20 x 1.5

Material: galvanized steel
Sound insulation insert: EPDM, black

Item code	Size range (mm)	Material	Thread	Weight (kg)
116766	11–15	20 x 1.0	M8/M10	0.04
116767	15–19	20 x 1.0	M8/M10	0.04
116768	20–24	20 x 1.0	M8/M10	0.04
116769	25–28	20 x 1.0	M8/M10	0.04
116771	32–35	20 x 1.0	M8/M10	0.06
116772	39–46	20 x 1.2	M8/M10	0.06
116773	48–53	20 x 1.2	M8/M10	0.08
116774	54–58	20 x 1.2	M8/M10	0.08
116775	59–66	20 x 1.2	M8/M10	0.08
116776	75–80	20 x 1.5	M8/M10	0.10
116777	87–92	20 x 1.5	M8/M10	0.12
116778	107–115	20 x 1.5	M8/M10	0.14
K117506	120–128	20 x 2.0	M8/M10	0.203

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
116766	ERS 11 - 15	0.04	200
116767		0.04	180
116768		0.04	170
116769		0.04	130
116771		0.06	120
116772		0.06	90
116773		0.08	70
116774		0.08	50
116775		0.08	50
116776		0.1	60
116777		0.12	50
116778		0.14	50
K117506	COLLARE ERS 120-128 MM	0.14	40