
STABIL D-M16 WITH SILICONE LINING





APPLICATION

Connection element for Stabil D-3G pipe clamps sizes 3/8" up to 3/4" (with sound absorption lining up to 1/2") for suspending pipe clamps underneath one another.

SCOPE OF DELIVERY

With silicone sound absorption lining (red); with welded on M16 nut; clamping bolts and nuts included in loose form. Other welded nuts (e.g. M20) or inch sockets available.

TECHNICAL DATA

The max. admissible load has been determined by using statistical methods resulting from the breaking loads, observing a max. admissible deformation of 1.5 mm resp. 2 % of the max. tensible pipe diameter.

Material:

- Clamp: Steel, electro-galvanised;

- Sound absorption lining: Silicone (see section "RUBBER PROFILE SAL SILICONE" for technical data).

Size range[mm]	Max. adm.load tension [kN]	Tightening torque [Nm]	Material [mm]	Clampingbolts	B [mm]	L [mm]
315 - 324	9	20	50 x 5	M16 x 60	454	404
345 - 356	9	20	50 x 5	M16 x 60	482	432
359 - 368	9	20	50 x 5	M16 x 60	496	446
398 - 407	9	20	50 x 5	M16 x 60	534	484

Codice	Nome	Peso	Numero di pezzi
146007	315 - 324 mm 12"	3.7	1
146016	345 - 356 mm 14"	3.13	1
146025	359 - 368 mm	3.57	1
146034	398 - 407 mm 16"	3.66	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
146043	410 - 419 mm	1.28	1
146052	495 - 508 mm 20''	1.49	1
146061	512 - 521 mm	0.3	1