
DUO CLAMP SRS WITH LINING





APPLICATION

Two-piece pipe clamp with double thread connection (M8/M10) and sound absorption lining for the installation of pipelines. Applicable for sound-absorbed installations according to DIN 4109 specifications.

SCOPE OF DELIVERY

Supplied with two bolts partially mounted on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidental unscrewing..

TECHNICAL DATA

Material:

- Clamp: Steel, electro-galvanised ;
- Sound absorption lining: SBR/EPDM, black (see section "RUBBER PROFILE SAL SBR/EPDM" for technical data).

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Size range[mm]	NB	Max. adm. load [kN]	Tightening torque[Nm]	MaterialW x th[mm]
12 - 15	1/4"	0,6	2	20 x 1.5
15 - 19	3/8"	0,6	2	20 x 1.5
20 - 23	1/2"	0,6	2	20 x 1.5
25 - 28	3/4"	0,6	2	20 x 1.5
32 - 35	1"	0,6	2	20 x 1.5
40 - 45	1 1/4"	0,6	2	20 x 1.5
48 - 52	1 1/2"	0,6	2	20 x 1.5
52 - 58		0,6	2	20 x 1.5
60 - 64	2"	0,6	2	20 x 1.5
67 - 72		2,5	2	25 x 2.0
73 - 80	2 1/2"	2,5	2	25 x 2.0
81 - 87		2,5	2	25 x 2.0
86 - 91	3"	2,5	2	25 x 2.0
102 - 108		2,5	2	25 x 2.0
110 - 115	4"	2,5	2	25 x 2.5
120 - 128		2,5	2	25 x 2.5
135 - 143		2,5	2	25 x 2.5
149 - 161		2,5	2	25 x 2.5
162 - 170		2,5	2	25 x 2.5
198 - 207		2,5	2	25 x 2.5
207 - 219		2,5	2	25 x 2.5

Codice	Nome	Peso	Numero di pezzi
159368	12 - 15 mm ¼''	0.05	100
159377	15 - 19 mm 3/8''	0.05	100
159386	20 - 23 mm ½''	0.06	100
159395	25 - 28 mm ¾''	0.07	100
159401	32 - 35 mm 1''	0.07	100
159614	40 - 45 mm 1 ¼''	0.09	50
159623	48 - 52 mm 1 ½''	0.1	50
179003	52 - 58 mm	0.1	50

Codice	Nome	Peso	Numero di pezzi
159632	60 - 64 mm 2''	0.11	50
179012	67 - 72 mm	0.19	25
159641	73 - 80 mm 2 ½''	0.2	25
192665	81 - 87 mm	0.05	25
159650	86 - 91 mm 3''	0.22	25
179021	102 - 108 mm	0.25	25
159669	110 - 115 mm 4''	0.3	25
191459	120 - 128 mm	0.34	25
191477	135 - 143 mm 5''	0.37	25
191486	149 - 161 mm	0.39	25
191468	162 - 170 mm 6''	0.4	25
191495	198 - 207 mm	0.48	25
191504	207 - 219 mm 8''	0.52	20