U-BOLTS 3570 A



APPLICATION

For pipeline systems in industrial and residential buildings and Sprinkler installations according to VdS and FM standards.

For horizontal and vertical pipelines, the U-Bolts are applied as Fixed Points and as Guiding Supports.

SCOPE OF DELIVERY

Four hexagon nuts included in loose form.

INSTALLATION

When used as Guided Support, nuts have to be arranged and fixed on both sides, at the top and at the bottom of the profile. Thereby the pipe should remain flexible. When used as Fixed Point the admissible loads of the connecting elements shouldn't exceed the bending loads of the U-bolt.

TECHNICAL DATA

Material: Steel, HCP.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	NB	B [mm]	L1 [mm]	L2 [mm]	Thread
26.9	3/4"	40	60	40	M 10
33.7	1"	48	66	40	M 10
42.4	1 1/4"	56	76	50	M 10
48.3	1 1/2"	62	82	50	M 10
60.3	2"	76	97	50	M 12
76.1	2 1/2"	94	113	50	M 12
88.9	3"	106	126	50	M 12
114.3	4"	136	155	60	M 16
139.7	5"	164	175	60	M 16
168.3	6"	192	201	60	M 16
193.7	202	218	233	60	M 16
219.1	8"	248	263	70	M 20
274.0	10"	302	314	70	M 20
323.9	12"	352	365	70	M 20
355.6	378	402	411	70	M 24
406.4	428	452	463	70	M 24
508.0	530	554	565	70	M 24

Codice	Nome	Peso	Numero di pezzi
404662	U-BOLT DIN 3570 A HCP M10X1/2	0.12	50
162179	26,9 mm ¾''	0.12	50
162188	33,7 mm 1''	0.12	50
162197	42,4 mm 1 ¼''	0.14	50
162203	48,3 mm 1 ½''	0.14	50
162212	60,3 mm 2''	0.23	50
162221	76,1 mm 2 ½''	0.26	50
162230	88,9 mm 3''	0.29	50
162249	114,3 mm 4''	0.63	25
162258	139,7 mm 5''	0.71	25
162267	168,3 mm 6''	0.8	10
162276	193,7 mm	0.9	10

Codice	Nome	Peso	Numero di pezzi
162285	219,1 mm 8''	1.61	10
162294	274,0 mm 10''	1.88	10
162300	323,9 mm 12''	2.15	1
162319	355,6 mm	3.53	1
162328	406,4 mm	3.9	1
162337	508,0 mm	4.63	1