

STABIL D-3G WITH SILICONE LINING







APPLICATION

For soundproof installation of pipes in M&E services and plant construction (as per DIN 4109)

SCOPE OF DELIVERY

With silicone sound absorption lining (red); with welded on M16 nut; clamping bolts and nuts included in loose form. Other welded nuts (e.g. M20) or inch sockets available.

TECHNICAL DATA

The max. admissible load has been determined by using statistical methods resulting from the breaking loads, observing a max. admissible deformation of 1.5 mm resp. 2 % of the max. tensible pipe diameter.

Material:
- Clamp: Steel, electro-galvanised;
- Sound absorption lining: Silicone (see section "RUBBER PROFILE SAL SILICONE" for technical data).

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Size range[mm]	NB	Max working load [kN]	Tightening torque[Nm]	MaterialW x th[mm]	Threadconnection	B [mm]
14 - 18	3/8"	1,8	2	25 x 2.0	M16/M10/M8	63
19 - 23	1/2"	1,8	2	25 x 2.0	M16/M10/M8	69
24 - 28	3/4"	2,0	3	30 x 2.5	M16/M10/M8	74
29 - 33	1 "	2,0	3	30 x 2.5	M16/M10/M8	81
33 - 37		2,0	3	30 x 2.5	M16/M10/M8	85
40 - 45	1 1/4"	2,0	3	30 x 2.5	M16/M10/M8	94
47 - 52	1 1/2"	2,0	3	30 x 2.5	M16/M10/M8	104
53 - 58		2,0	3	30 x 2.5	M16/M10/M8	110
60 - 65	2"	2,0	3	30 x 2.5	M16/M10/M8	117
67 - 72 M		2,0	3	30 x 3.0	M16/M10/M8	137
73 - 78 M	2 1/2"	2,0	3	30 x 3.0	M16/M10/M8	143
79 - 85 M		2,0	3	30 x 3.0	M16/M10/M8	149
88 - 93 M	3"	2,0	3	30 x 3.0	M16/M10/M8	157
100 - 106 M		2,0	3	30 x 3.0	M16/M10/M8	171
108 - 115 M	4"	2,0	3	30 x 3.0	M16/M10/M8	180
124 - 129		2,9	5	40 x 4.0	1/2"/M16/M12	210
131 - 137		2,9	5	40 x 4.0	1/2"/M16/M12	218
138 - 144	5"	2,9	5	40 x 4.0	1/2"/M16/M12	225
148 - 154		2,9	5	40 x 4.0	1/2"/M16/M12	235
156 - 162		2,9	5	40 x 4.0	1/2"/M16/M12	243
165 - 171	6"	8,0	10	40 x 4.0	1/2"/M16/M12	255
177 - 183		8,0	10	40 x 4.0	1/2"/M16/M12	265
188 - 194		8,0	10	40 x 4.0	1/2"/M16/M12	276
196 - 203		8,0	10	40 x 4.0	1/2"/M16/M12	287
205 - 214		8,0	10	40 x 4.0	1/2"/M16/M12	296
219 - 225	8"	8,0	10	40 x 4.0	1/2"/M16/M12	307
244 - 250		8,0	10	40 x 4.0	1/2"/M16/M12	332
267 - 273	10"	8,0	10	40 x 4.0	1/2"/M16/M12	355
299 - 305		8,0	10	40 x 4.0	1/2"/M16/M12	387

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVALS

VdS Approval No. G4920027.

This product has been awarded the RAL quality marks "pipe supports" and is subject to continuous external monitoring according to RAL GZ-655.

Codice	Nome	Peso	Numero di pezzi
108070	14 - 18 mm 3/8''	0.08	50
108089	19 - 23 mm ½''	0.09	50
108098	24 - 28 mm ¾''	0.13	50
108104	29 - 33 mm 1 ''	0.14	50
108113	33 - 37 mm	0.15	50
108122	40 - 45 mm 1 ¼''	0.16	50
108131	47 - 52 mm 1 ½''	0.19	50
108140	53 - 58 mm	0.2	50
108159	60 - 65 mm 2''	0.21	50
115801	73 - 78 mm M 2 ½''	0.31	25
115802	73 - 78 mm M 2 ½''	0.33	25
115804	88 - 93 mm M 3''	0.32	25
115805	88 - 93 mm M 3''	0.37	25
115806	108 - 115 mm M 4	0.4	25
115807	108 - 115 mm M 4	0.43	25
108229	124 - 129 mm	0.87	10
108238	131 - 137 mm	0.91	10
108274	138 - 144 mm 5''	0.94	10
108283	148 - 154 mm	1	10
108292	156 - 162 mm	1.05	10
108308	165 - 171 mm 6''	1.14	10
108317	177 - 183 mm	1.18	10

Codice	Nome	Peso	Numero di pezzi
108326	188 - 194 mm	1.23	10
154947	196 - 203 mm	1.3	10
149879	205 - 214 mm	1.4	10
108335	219 - 225 mm 8''	1.4	10
108344	244 - 250 mm	1.51	10
108353	267 - 273 mm 10''	1.71	10
108362	299 - 305 mm	1.79	10