STABIL D-3G EPDM HCP



APPLICATION

For the installation of pipes required for all M&E services in industrial, residential and public buildings.

SCOPE OF DELIVERY

Sizes 15 to 129 mm are equipped with welded nuts for the clamping bolts. On the joint side, the clamping bolt is pre-assembled; the clamping bolt on the opposite side is mounted into the bore hole and retained by a plastic washer, thus preventing any accidental unscrewing.

For sizes 133 and larger the clamping bolts and the required nuts are supplied in loose form.

With welded in 3G triple thread nut; without sound absorption lining.

TECHNICAL DATA

Size [mm]	Max. working load (Tension)
10 - 72	4,0 kN
76 - 129	5,0 kN
133 - 173	8,0 kN
176 - 316	12,5 kN

(Tension)

MATERIAL

Steel, HCP.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Ø [mm]	NB	Material W x th [mm]	Thread connection	B [mm]
10 - 14		25 x 2.0	M16/M10/M8	60
15 - 19	3/8"	25 x 2.0	M16/M10/M8	57
20 - 24	1/2"	25 x 2.0	M16/M10/M8	63
25 - 30	3/4"	25 x 2.0	M16/M10/M8	69
31 - 35 *	1"	30 x 2.5	M16/M10/M8	74
36 - 41		30 x 2.5	M16/M10/M8	81
40 - 45 *	1 1/4"	30 x 2.5	M16/M10/M8	85
48 - 53 *	1 1/2"	30 x 2.5	M16/M10/M8	94
54 - 59		30 x 2.5	M16/M10/M8	101
60 - 65 *	2"	30 x 2.5	M16/M10/M8	108
67 - 72		30 x 2.5	M16/M10/M8	114
76 - 81 M *	2 1/2"	30 x 3.0	M16/M10/M8	137
82 - 87 M		30 x 3.0	M16/M10/M8	143
88 - 93 M *	3"	30 x 3.0	M16/M10/M8	149
102 - 108 M		30 x 3.0	M16/M10/M8	163
110 - 116 M *	4"	30 x 3.0	M16/M10/M8	171
124 - 129 M		30 x 3.0	M16/M10/M8	184
133 - 140		40 x 4.0	1/2"/M16/M12	210
140 - 148 *	5"	40 x 4.0	1/2"/M16/M12	218
149 - 155		40 x 4.0	1/2"/M16/M12	225
159 - 165		40 x 4.0	1/2"/M16/M12	235
167 - 173 *	6"	40 x 4.0	1/2"/M16/M12	243
176 - 184		40 x 4.0	1/2"/M16/M12	255
188 - 194		40 x 4.0	1/2"/M16/M12	265
199 - 205		40 x 4.0	1/2"/M16/M12	276
207 - 216		40 x 4.0	1/2"/M16/M12	287
219 - 225	8"	40 x 4.0	1/2"/M16/M12	296
244 - 250		40 x 4.0	1/2"/M16/M12	321
267 - 273	10"	40 x 4.0	1/2"/M16/M12	344
278 - 284		40 x 4.0	1/2"/M16/M12	355
297 - 303		40 x 4.0	1/2"/M16/M12	374
310 - 316		40 x 4.0	1/2"/M16/M12	387

[mm]

W x th

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

[mm]

connection

[mm]

APPROVALS:

VdS-Approval No. G4920027, * = FM Approval

Codice	Nome	Peso	Numero di pezzi
112249	14 - 18 mm 3/8''	0.08	50
112250	19 - 23 mm ½''	0.09	50
112251	24 - 28 mm ¾''	0.12	50
112252	29 - 33 mm 1''	0.14	50
112253	33 - 37 mm	0.15	50
112254	40 - 45 mm 1 ¼''	0.16	50
112255	47 - 52 mm 1 ½''	0.18	50
112256	53 - 58 mm	0.19	50
112257	60 - 65 mm 2''	0.21	50
115782	73 - 78 mm	0.33	25
115784	108 - 115 mm 4''	0.43	25
115785	STABIL D-3G EPDM 100-106 HCP	0.41	25
115786	108 - 115 mm 4''	0.43	25
112266	124 - 129 mm	0.86	10
112267	131 - 137 mm	0.9	10
112268	138 - 144 mm 5''	0.94	10
112269	148 - 154 mm	0.98	10
112270	156 - 162 mm	1.02	10
112271	165 - 171 mm 6''	1.08	10
112272	177 - 183 mm	1.18	10
112273	188 - 194 mm	1.22	10

Codice	Nome	Peso	Numero di pezzi
112274	196 - 203 mm	1.29	10
112275	205 - 214 mm	1.32	10
112276	219 - 225 mm 8''	1.38	10
112278	244 - 250 mm	1.52	10
112280	267 - 273 mm 10''	1.6	10
112281	278 - 284 mm	1.67	10
112282	299 - 305 mm	1.76	10
112283	307 - 318 mm	1.83	10