
BLOCKSET BPS CC 27



APPLICATION

Quick-installation element for efficient mounting of pipe clamps and other components to Channels 27/27 and 27/15.

Advantages:

- Time-saving due to a pre-assembled Blockset consisting of 4 individual parts;

- Easy height adjustment within the channel;

- Retains position in horizontal and vertical channels during locational adjustment. But still can be moved easily and freely along the channel as required;

- Grooved rod, prevents unintended unscrewing;

- Easy cutting of the grooved rod - cutting grooves every 10 mm using Rod Cutter PBC 1.

SCOPE OF DELIVERY

Completely pre-assembled (block with holding bracket, grooved rod and nut).

INSTALLATION

Insert the Blockset into the channel, then tighten the nut to 10 Nm - That's it!

TECHNICAL DATA

Max. working load:

- Fz = 1,5 kN

- Fx = 0,8 kN

- Fy = Permissible lateral force at the end of the grooved rod

Type[mm]	L [mm]	Fy
M8 x 35	35	75
M8 x 75	75	35
M8 x125	125	20
M8 x 175	175	-
M8 x 275	275	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Material:Steel, electro-galvanised.

Codice	Nome	Peso	Numero di pezzi
195888	M8 × 35 mm	0.04	100
195895	M8 × 75 mm	0.05	100
195901	M8 × 125 mm	0.06	50
195918	M8 × 175 mm	0.07	50
195925	M8 × 275 mm	0.1	50