
BEAM BRACKET TKO F 80



APPLICATION

Galvanised hollow-box-section with welded end-plate to serve as cantilever arm. May be used as a crossbar when combined with End Support STA/End Support WBD and 4 x Self Forming Screw FLS .

SCOPE OF DELIVERY

With pre-assembled End Cap ADK F 80.

INSTALLATION

Depending on the situation, different options are recommended:

a) Directly to building structure: 4 x suitable wall anchors

b) To traditional steel beams between 80 – 120 mm flange dimensions: 1x Assembly Set 5P M12 S

c) To traditional steel beams > 120 flange dimension: with on-demand Adaptor Plate (tbc)

d) To Steel Beams 100/120: with Bracket Plates FV 100/120 when positive mechanical connection required

TECHNICAL DATA

Type	L[mm]	Dimensions of base plate[mm]	Slots in base plate for
TKO F80-400	400	220 x 220 x 12	M12
TKO F80-800	800	220 x 220 x 12	M12

Configuration: Base plate welded to Beam Section TP F 80.

Material:

- Base plate: Steel, HCP;
- Beam section: Steel, HCP.

APPROVALS

CE mark, according to EN 1090; MPA tested.

CE

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
192788	TKO F 80 L=400mm	6.6	1
192795	TKO F 80 L=800mm	9.2	1