SAFETY STRAP SL VDS



APPLICATION

Additional safety feature for Beam Clamps supporting tubes of nominal diameter NB 80 and larger, required for installations meeting the Vds standard.

Dimensions and material meet the VdS CEA-guideline for Sprinkler systems.

INSTALLATION

The safety strap is bent on the construction site to the form of the beam, so that it securely encompasses the edge of the beam flange.

TECHNICAL DATA

Material: Steelstrip, pre-galvanised.

Application:

Type I: NB 80 - NB 100

Type II: NB 125 - NB 150

Type III: NB 200

Type	Lenght[mm]	Bore[mm]	Dimensionsb x s [mm]
I M10	400	11	20 x 2,5
II M12	400	13	30 x 2,5
III M16	400	17	40 x 3,0

Codice	Nome	Peso	Numero di pezzi
116798	Tipo I M10	0.16	50
116804	Tipo II M12	0.23	50
116813	Tipo III M16	0.36	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com