



SPEED NUT NT CC 41 SS



APPLICATION

In particular useful when installing in vertical channels or in places of difficult access.

Further advantages:

- For all Channels of type 41, independent of the height of the channel;
- No getting stuck on bolt heads when sliding in the channel;
- No appearance of settlement after tightening.

SCOPE OF DELIVERY

Channel Nut and Spring are tightly connected.

INSTALLATION

After inserting the Speed Nut into the channel opening, it is - by exerting slight pressure on it - turned to the right as far as it will go; deinstallation may be effected by following the instructions in reverse order.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Installation and deinstallation do not require tools and may be repeated several times.

TECHNICAL DATA

	M6	M8	M10
Tightening torque [Nm]	10	25	40

Material thickness channel [mm]	M6 FZ ≤ [kN]	M8 FZ ≤ [kN]	M10 FZ ≤ [kN]		M6 FQ ≤ [kN]	M8 FQ ≤ [kN]	M10 FQ ≤ [kN]
2.0	3.2	5.8	5.8		0.9	2.1	3.4
2.5	3.2	5.8	5.8		1.0	2.6	4.1

Note: The admissible load capacities of the channels are to be taken into account. Material: - Nut: Stainless steel 316 (A4);- Spring: Sheet metal spring steel, rustproof.

Codice	Nome	Peso	Numero di pezzi
199299	CC 41-M 6 A4	0.03	50
199305	CC 41-M 8 A4	0.03	50
199312	CC 41-M10 A4	0.03	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com