

SPEED NUT NT CC 41 SS





APPLICATION

In particular useful when installing in vertical channels or in places of difficult access.

Further advantages:

- For all Channels of type 41, independent of the height of the channel;
- No getting stuck on bolt heads when sliding in the channel;
- No appearance of settlement after tightening.

SCOPE OF DELIVERY

Channel Nut and Spring are tightely connected.

INSTALLATION

After inserting the Speed Nut into the channel opening, it is - by exerting slight pressure on it - turned to the right as far as it will go; deinstallation may be effected by following the instructions in reverse order.

Installation and deinstallation do not require tools and may be repeated several times.

TECHNICAL DATA

	M6	M8	M10
Tightening torque [Nm]	10	25	40

Material thickness channel [mm]	M6 FZ ≤ [kN]	M8 FZ ≤ [kN]	M10 FZ ≤ [kN]		M6 FQ ≤ [kN]	M8 FQ ≤ [kN]	M10 FQ ≤ [kN]
2.0	3.2	5.8	5.8		0.9	2.1	3.4
2.5	3.2	5.8	5.8		1.0	2.6	4.1

Note: The admissible load capacities of the channels are to be taken into account.

Material:
- Nut: Stainless steel 316 (A4);
- Spring: Sheet metal spring steel, rustproof.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
199299	CC 41-M 6 A4	0.03	50
199305	CC 41-M 8 A4	0.03	50
199312	CC 41-M10 A4	0.03	50