
BLOCK BP 27



APPLICATION

Quick-installation element for efficient mounting of pipe clamps and other components to Channels 27/27 and 27/15:

- Time-saving due to pre-assembled Block instead of 2 individual parts;

- Retains position in horizontal and vertical channels during locational adjustment. But can still be moved easily and freely along the channel as required.

- To be combined with Pressix Rods PNS, threaded rods, screws or other products with a thread connection.

SCOPE OF DELIVERY

Block completely pre-assembled. Installation

Insert the Block into the channel; by turning to the right, the channel nut locks into the channel, then tighten up to 10 Nm - That's it!

Note:Thread connection M10 practicable by using Reducer f/m 10/8

TECHNICAL DATA

Max. work load:

- Fz = 1.5 kN

- Fx = 0.8 kN

Material: Steel, electro-galvanised.

Codice	Nome	Peso	Numero di pezzi
195932	PB 27	0.01	100
117357	PB 27 M10	0.01	100

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com