

FIXING BRACKET MW S







APPLICATION

Designed for general mounting purposes as a direct lateral attachment link integrated in binding and bridging beams of concrete or wood, and for similar applications. It may serve as a connecting bracket for framework structures consisting of channels.

Types 60/30/90 and 90/60/90 are designed for attachment of pipes to wooden truss according to VdS CEA-standard 15.2.2.

TECHNICAL DATA

Material:Angle steel profile, electro-galvanised.

Type	Working load [kN]	B [mm]	b [mm]	d [mm]	s [mm]
45/30/90°	3.5	30	13	11	-
70/40/90°	2.0	40	17/35	10,5	-
60/40/90°	7.5	40	20	13	-
90/60/90°	7.5	40	15	13	50

Note: for Sprinkler systems, application of 60/30/90 and 90/60/90 to wooden truss.

Single Bracket with wooden screw

Double Bracket with threaded bolt

"d" depending on NB:

≤ NB 50: 2 x 6 mm
> NB 50 ≤ DN 100: 2 x 8 mm
> NB 100 ≤ DN 150: 2 x 10 mm

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
115380	S 45/30	0.07	50
115399	S 60/40	0.17	25
114820	S 90/60	0.26	25

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com