



# SLIDE ELEMENT GLE LC



## APPLICATION

Suspension slide element which can be fixed as a single mounting element directly to the ceiling or, in case of parallel pipe runs, to Channels.

Pendular function allows for slight lateral movements.

The slide roller located in the suspending section provides for smooth, jerk-free and silent sliding.

For Type LC-A an additional extension is not needed, if a directed preselection of the thread length is done; especially suitable for different isolation.

## SCOPE OF DELIVERY

Completely pre-assembled.

## INSTALLATION

Type LC-I allows for height adjustment by offering a screw depth of up to 15 mm.

For fixing the position of the Slide Element, a locking nut has to be used.

## TECHNICAL DATA

Working load (tension): 1 kN

Sliding distance: max. 25 mm

Maximum swinging angle: 2°

Material: Steel, electro-galvanised

Type	Thread connection to building structure	Thread connection to system x L	Height H [mm]
LC-A 22	M8 x 22	M8 x 22	76
LC-I	M8 x 22	M8 /15*	68

\* range for height adjustment

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

<b>Codice</b>	<b>Nome</b>	<b>Peso</b>	<b>Numero di pezzi</b>
151069	LC-A	0.09	100
151078	LC-IF	0.09	100

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)