


STABIL D-3G









APPLICATION

For installation of pipes required for all M&E services in industrial, residential and public buildings.

SCOPE OF DELIVERY

Sizes 15 to 129 mm are equipped with welded nuts for the clamping bolts. On the joint side, the clamping bolt is pre-assembled; the clamping bolt on the opposite side is mounted into the bore hole and retained by a plastic washer, thus preventing any accidental unscrewing.

For sizes 133 and larger the clamping bolts and the required nuts are supplied in loose form.

With welded in 3G triple thread nut; without sound absorption lining. For further adapter-based connection options via the external thread of the 3G triple thread nut, see product "ADAPTER AD F/F".

TECHNICAL DATA

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Size range[mm]	NB	Working load [kN]	B [mm]	Material [mm]	Thread connection
15 - 19	3/8"	4,0	57	25 x 2,0	M16/M10/M8
20 - 24	1/2"	4,0	63	25 x 2,0	M16/M10/M8
25 - 30	3/4"	4,0	69	25 x 2,0	M16/M10/M8
31 - 35 *	1"	4,0	74	30 x 2,5	M16/M10/M8
40 - 45 *	1 1/4"	4,0	85	30 x 2,5	M16/M10/M8
48 - 53 *	1 1/2"	4,0	94	30 x 2,5	M16/M10/M8
54 - 59 *		4,0	101	30 x 2,5	M16/M10/M8
60 - 65 *	2"	4,0	108	30 x 2,5	M16/M10/M8
67 - 72 *		4,0	114	30 x 2,5	M16/M10/M8
76 - 81 M *	2 1/2"	5,0	137	30 x 3,0	M16/M10/M8
82 - 87 M *		5,0	143	30 x 3,0	M16/M10/M8
88 - 93 M *	3"	5,0	149	30 x 3,0	M16/M10/M8
102 - 108 M *		5,0	163	30 x 3,0	M16/M10/M8
110 - 116 M *	4"	5,0	171	30 x 3,0	M16/M10/M8
124 - 129 M *		5,0	184	30 x 3,0	M16/M10/M8
133 - 140 *		8,0	210	40 x 4,0	1/2"/M16/M12
140 - 148 *	5"	8,0	218	40 x 4,0	1/2"/M16/M12
149 - 155 *		8,0	225	40 x 4,0	1/2"/M16/M12
159 - 165 *		8,0	235	40 x 4,0	1/2"/M16/M12
167 - 173 *	6"	8,0	243	40 x 4,0	1/2"/M16/M12
176 - 184		12,5	255	40 x 4,0	1/2"/M16/M12
188 - 194		12,5	265	40 x 4,0	1/2"/M16/M12
199 - 205		12,5	276	40 x 4,0	1/2"/M16/M12
207 - 216		12,5	287	40 x 4,0	1/2"/M16/M12
219 - 225	8"	12,5	296	40 x 4,0	1/2"/M16/M12
244 - 250		12,5	321	40 x 4,0	1/2"/M16/M12
267 - 273	10"	12,5	344	40 x 4,0	1/2"/M16/M12
278 - 284		12,5	355	40 x 4,0	1/2"/M16/M12
297 - 303		12,5	374	40 x 4,0	1/2"/M16/M12
310 - 316		12,5	387	40 x 4,0	1/2"/M16/M12

APPROVAL

VdS-Approval No. G4920027.

* = FM Approval (another pipe clamp with FM Approval is: Stabil D-M16).

Codice	Nome	Peso	Numero di pezzi
107705	15 - 19 mm 3/8''	0.07	50
107714	20 - 24 mm ½''	0.08	50
107723	25 - 30 mm ¾''	0.08	50
107015	31 - 35 mm * 1''	0.12	50
107024	40 - 45 mm * 1 ¼''	0.13	50
107033	48 - 53 mm * 1 ½''	0.15	50
107042	54 - 59 mm	0.16	50
107051	60 - 65 mm * 2''	0.17	50
107060	67 - 72 mm	0.18	50
115759	76 - 81 mm M * 2 ½''	0.28	25
115761		0.29	25
115762	88 - 93 mm M * 3''	0.31	25
115763		0.34	25
115764	110 - 116 mm M * 4''	0.36	25
115766		0.39	25
107130	133 - 140 mm	0.76	10
115885	140 - 148 mm * 5''	0.78	10
107149	149 - 155 mm	0.8	10
107158	159 - 165 mm	0.82	10
107167	167 - 173 mm * 6''	0.9	10
107176	176 - 184 mm	0.99	10
107185	188 - 194 mm	1.01	10
107194	199 - 205 mm	1.05	10
148939	207 - 216 mm	1.11	10
107200	219 - 225 mm 8''	1.12	10

Codice	Nome	Peso	Numero di pezzi
107219	244 - 250 mm	1.25	10
107228	267 - 273 mm 10''	1.33	10
107237	278 - 284 mm	1.36	10
107246	297 - 303 mm	1.44	10
147600	310 - 316 mm	1.48	10