


COLLARE AKS







APPLICATION

Suitable for secure prevention of condensation at the pipe support location of chilled-water and cold-water pipelines as well as insulation clamp for heating systems.
Suitable for soundproof installation according to DIN 4109.

SCOPE OF DELIVERY

Consisting of pipe clamp and insulation insert.

INSTALLATION

Enclose the insulation insert around the pipe, remove the protective paper strip on both sides of the insert and merge the longitudinal seam. Fix the pipe clamp in the centre of the plastic spacers. Lag the pipe insulation to each end of the insulation insert.

For horizontal installations to a wall-face, the plastic spacers on the insulation insert have to coincide with the pipe clamp flanges positioned over and under the pipe.

TECHNICAL DATA

Material of pipe clamp: Steel, electro-galvanised
Insulation: Elastomer foam

Elastomer foam:
Length b: 80 mm
Thermal conductivity: λ ≤ 0,038 W/(mK) at 0°C
Steam diffusion resistance factor: μ ≥ 7.000
Material class: BL -s3, d0 (in overall system of identical Elastomer foam)
Temperature range: 0°C up to +110°C
Storage conditions: In dry, clean rooms with humidity 50 - 70% and room temperature 0 - 35°C

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
113429	13 - 10 mm	0.07	50
113430	13 - 12 mm	0.08	50
113431	13 - 15 mm	0.08	50
113432	13 - 18 mm	0.08	50
113433	13 - 22 mm	0.09	50
113434	13 - 25 mm	0.09	50
113435	13 - 28 mm	0.1	50
113436	13 - 30 mm	0.1	50
113437	13 - 35 mm	0.11	50
113438	13 - 42 mm	0.12	30
113439	13 - 48 mm	0.18	30
113440	13 - 54 mm	0.18	30
113441	13 - 60 mm	0.2	30