


GUIDING SET FS

APPLICATION

Element for completing Guided Pipe Shoes based on Sliding Pipe Shoes.

Max. beam flange width t ≤ 30 mm

SCOPE OF DELIVERY

Pre-assembled Guiding Set containing:

- 4 Clamping hooks;
- 2 Grub screws;
- Lift-off preventions:
  2 for FS 240/260;
  4 for FS 280/300;
- Hexagon nuts:
  4 for FS 80/120, FS 140/160 and FS 180/220 each;
  8 for FS 240/260 and 12 for FS 280/300.

TECHNICAL DATA

Material:

- Metal sheets: Steel, HCP;
- Grub screws, nuts: Steel, HCP;
- Clamping hooks: Cast iron, HCP.

Type	For flange width [mm]
XS 80/120	80 - 120
XS 140/160	140 - 160
XS 180/220	180 - 220
XS 240/260	240 - 260
XS 280/300	280 - 300

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVALS

Certification of quality TUV-Rheinland nr.102793.

Codice	Nome	Peso	Numero di pezzi
110350	FS 80/120	2	-
110351	FS 140/160	2.15	-
110352	FS 180/220	2.3	-
110353	FS 240/260	2.8	-
112887	FS 280/300	3.26	-