


# GLASS FIBRE TAPE GSK



## APPLICATION

Inlay for pipe clamps for thermic and galvanic separation (prevention of contact corrosion). The Glass Fabric Tape is classified in the hydrolytic class I (best class) according to DIN 12111 regarding resistance to water. So it has an excellent resistance to acid and neutral solutions.

## SCOPE OF DELIVERY

In rolls, self-adhesive on one side, coated with PE peel-off foil on the adhesive side.

## TECHNICAL DATA

Temperature range: Up to +500°C permanent exposure  
Density: 2,6 g/cm<sup>3</sup>  
Tensile strength: 3.400 - 3.700 N/mm<sup>2</sup>  
Resistant to: Oils, greases, solvents and organic acids.

Codice	Nome	Peso	Numero di pezzi
114865		0.04	10
114866		0.06	10
114867		0.07	10
114868		0.09	10
114869		0.1	10

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)