DUO CLAMP SRS SS W/LINING



APPLICATION

Two-piece pipe clamp with thread connection M8 or M10 and sound absorption lining for the installation of pipelines.

SCOPE OF DELIVERY

Supplied with two bolts pre-screwed on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidental unscrewing.

TECHNICAL DATA

Size range[mm]	For pipe[NB]	Max. perm.working load [kN]	Tightening torque[Nm]	Threadconnection	MaterialW x th[mm]
12 - 15	1/4"	0,6	2	M8	20 x 1.5
15 - 19	3/8"	0,6	2	M8	20 x 1.5
20 - 23	1/2"	0,6	2	M8	20 x 1.5
25 - 28	3/4"	0,6	2	M8	20 x 1.5
32 - 35	1"	0,6	2	M8	20 x 1.5
40 - 45	1 1/4"	0,6	2	M8	20 x 1.5
48 - 52	1 1/2"	0,6	2	M8	20 x 1.5
52 - 58	-	0,6	2	M8	20 x 1.5
60 - 64	2"	0,6	2	M8	20 x 1.5
67 - 72	-	2,5	2	M10	25 x 2.0
73 - 80	2 1/2"	2,5	2	M10	25 x 2.0
86 - 91	3"	2,5	2	M10	25 x 2.0
102 - 108	-	2,5	2	M10	25 x 2.0
110 - 115	4"	2,5	2	M10	25 x 2.5
135 - 143	5"	2,5	2	M10	25 x 2.5
149 - 161	-	2,5	2	M10	25 x 2.5
162 - 170	6"	2,5	2	M10	25 x 2.5

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Material:

- Pipe clamp: Stainless steel A4;

- Sound absorption lining: SBR/EPDM, black (see section "RUBBER PROFILE SAL SBR/EPDM" for technical data).

Codice	Nome	Peso	Numero di pezzi
170693	12 - 15 mm ¼''	0.05	100
170709	15 - 19 mm 3/8''	0.06	100
170718	20 - 23 mm ½''	0.06	100
170727	25 - 28 mm ¾''	0.06	100
170736	32 - 35 mm 1''	0.07	100
170745	40 - 45 mm 1 ¼''	0.08	50
170754	48 - 52 mm 1 ½''	0.09	50
173360	52 - 58 mm	0.09	50
170763	60 - 64 mm 2''	0.1	50
173369	67 - 72 mm	0.19	25
170772	73 - 80 mm 2 ½''	0.2	25
170781	86 - 91 mm 3''	0.22	25
173378	102 - 108 mm	0.25	25
170790	110 - 115 mm 4''	0.29	25
110884	135 - 143 mm 5''	0.36	25
110885	149 - 161 mm	0.39	25
110886	162 - 170 mm 6''	0.39	25