
STABIL D-A





31-72 mm



76 - 303 mm



324 - 521 mm

APPLICATION

For installation of pipes required for all M&E services in industrial, residential and public buildings. In combination with Triple Thread Connector NT 3G the suspension of pipe clamps up to dia. 303 mm is possible.

SCOPE OF DELIVERY

Two parts pipe clamp without clamping bolts and nuts. For suitable clamping bolts, see chapter "FIXINGS AND FASTENINGS".

TECHNICAL DATA

Material: steel, electro-galvanised.

Size range[mm]	NB	Max working load [kN]	B [mm]	L [mm]	Material W x th [mm]	Recommended clamping bolts
31 - 35	1"	4,0	70.5	52.5	30 x 2,5	M8 x 20
40 - 45	1 1/4"	4,0	82	64	30 x 2,5	M8 x 20
48 - 53	1 1/2"	4,0	90.5	72.5	30 x 2,5	M8 x 20
54 - 59		4,0	101	83	30 x 2,5	M8 x 20
60 - 65	2"	4,0	108	90	30 x 2,5	M8 x 20
67 - 72		4,0	114	96	30 x 2,5	M8 x 20
76 - 81	2 1/2"	5,0	137	115	30 x 3,0	M10 x 30
82 - 87		5,0	143	121	30 x 3,0	M10 x 30
88 - 93	3"	5,0	149	127	30 x 3,0	M10 x 30
102 - 108		5,0	163	141	30 x 3,0	M10 x 30
110 - 116	4"	5,0	171	149	30 x 3,0	M10 x 30
124 - 129		5,0	184	162	30 x 3,0	M10 x 30
133 - 140		10,0	210	181	40 x 4,0	M12 x 40
140 - 148	5"	10,0	218	189	40 x 4,0	M12 x 40
149 - 155		10,0	225	196	40 x 4,0	M12 x 40
159 - 165		10,0	235	206	40 x 4,0	M12 x 40
167 - 173	6"	10,0	243	214	40 x 4,0	M12 x 40
176 - 184		10,0	255	226	40 x 4,0	M12 x 45
188 - 194		10,0	265	236	40 x 4,0	M12 x 45
199 - 205		10,0	276	247	40 x 4,0	M12 x 45
207 - 216		10,0	287	258	40 x 4,0	M12 x 45
219 - 225	8"	10,0	296	267	40 x 4,0	M12 x 45
244 - 250		10,0	321	292	40 x 4,0	M12 x 45
267 - 273	10"	10,0	344	315	40 x 4,0	M12 x 45
278 - 284		10,0	355	326	40 x 4,0	M12 x 45
297 - 303		10,0	374	345	40 x 4,0	M12 x 45
316 - 324	324	12,5	440	390	50 x 5,0	M16 x 60
348 - 356	356	12,5	471	421	50 x 5,0	M16 x 60
360 - 368	368	12,5	482	432	50 x 5,0	M16 x 60
399 - 407	407	12,5	520	470	50 x 5,0	M16 x 60
411 - 419	419	12,5	532	482	70 x 6,0	M16 x 60
500 - 508	508	12,5	619	569	70 x 6,0	M16 x 60
513 - 521	521	12,5	631	581	70 x 6,0	M16 x 60

Codice	Nome	Peso	Numero di pezzi
113367	31 - 35 mm 1''	0.09	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
113368	40 - 45 mm 1 ¼''	0.1	50
113369	48 - 53 mm 1 ½''	0.14	50
113370	54 - 59 mm	0.16	50
113371	60 - 65 mm 2''	0.18	50
113372	67 - 72 mm	0.19	50
113373	76 - 81 mm 2 ½''	0.22	25
113374	82 - 87 mm	0.23	25
113375	88 - 93 mm 3''	0.25	25
113376	102 - 108 mm	0.28	25
113377	110 - 116 mm 4''	0.3	25
113378	124 - 129 mm	0.32	25
113379	133 - 140 mm	0.65	10
113380	140 - 148 mm 5''	0.66	10
113381	149 - 155 mm	0.72	10
113382	159 - 165 mm	0.72	10
113383	167 - 173 mm 6''	0.76	10
113384	176 - 184 mm	0.83	10
113385	188 - 194 mm	0.84	10
113386	199 - 205 mm	0.89	10
113387	207 - 216 mm	0.93	10
113388	219 - 225 mm 8''	0.96	10
113389	244 - 250 mm	1.02	10
113390	267 - 273 mm 10''	1.16	10
113391	278 - 284 mm	1.2	10
113392	297 - 303 mm	1.27	10
103701	316 - 324 mm 12''	2.35	1
103747	360 - 368 mm	2.54	1
103765	399 - 407 mm 16''	2.66	1
103783	411 - 419 mm	4.84	1
103808	500 - 508 mm 20''	5.78	1
103826	513 - 521 mm	5.67	1