SPEED NUT CC HCP



APPLICATION

In particular useful for installation in vertical channels or places of difficult access.

Further advantages:

- For all Channels of type 41, independent of the channel height.
- No getting stuck on bolt heads when sliding in the channel.
- No appearance of settlement after tightening.

SCOPE OF DELIVERY

Channel Nut and Spring are tightely connected.

INSTALLATION

After inserting the Speed Nut into the channel opening, it is turned to the right as far as it will go by exerting slight pressure on it; deinstallation may be effected by following the instructions on the reverse order.

Installation and deinstallation do not require tools and may be repeated several times.

TECHNICAL DATA

	M6	M8	M10	M12
Tightening torque 8.8 1) [Nm]	10	25	40	80

[1)] Using lower steel classes, the value are to be reduced accordingly.

Channel thickness [mm]	M6 FZ ≤ [kN]	M8 FZ ≤ [kN]	M10 FZ ≤ [kN]	M12 FZ ≤ [kN]		M6 FQ ≤ [kN]	M8 FQ ≤ [kN]	M10 FQ ≤ [kN]	M12 FQ ≤ [kN]
1.5	3.2	4.7	4.7	7.5		0.7	1.8	2.9	7.5
2.0	3.2	5.8	5.8	10		0.9	2.1	3.4	9
2.5	3.2	5.8	5.8	11		1.0	2.6	4.1	9
3.0	3.2	5.8	5.8	13		1.1	2.8	4.4	9

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Note: The permissible load capacities of the channels are to be respected.

Material:

- CC-Channel Nut: Steel class, HCP;
- Spring washer: Sheet metal spring steel, rustproof.

Codice	Nome	Peso	Numero di pezzi
198698	CC 41-M 6	0.03	50
198650	CC 41-M 8	0.03	50
186284	CC 41-M10	0.03	50
110015	CC 41-M12	0.06	50