
END SUPPORT STA F 100



APPLICATION

Plug-in component designed to create an endplate at the open end of a Beam Section TP F 100, TP F 100/160 or a Cantilever bracket AK F 100. Variation types F 100-80 (E) are designed to combine F 100 with F 80 beam sections; at the same time F 100/160 (E) are designed to combine F 100 with F 100/160 beam sections. Octagonal insert allows full utilisation of beam section within the space required by the End Support STA itself.

INSTALLATION

Depending on the situation, different options are recommended:

a) With 2x4 Self Forming Screws FLS when used to connect 2 Beam Sections; the Beam Section TP F 100/160 connected to the End Support STA F 100 - 100/160 has to be screwed with 8 Self Forming Screws FLS F. On each of the broader sides 4 Self Forming Screws FLS F are necessary.

b) With 4 Self Forming Screws FLS applied to the octagonal insert and 2 suitable wall anchors/fixings when connected to the building structure.

The Beam Section TP F 100/100 connected to the End Support STA F 100 has to be screwed with 4 Self Forming Screws FLS F. On each of the opposite sides 2 Self Forming Screws FLS F are necessary.

TECHNICAL DATA

Type	Dimensions of base plate[mm]	A[mm]	B[mm]	H[mm]
STA F 100	210 x 100 x 8	14	20 x 11	188
STA F 100-E	185 x 100 x 8	-	20 x 11	188
STA F 100-80	210 x 100 x 8	14	20 x 11	148
STA F 100-80-E	185 x 100 x 8	-	20 x 11	148
STA F 100 - 100/160	270 x 100 x 8	-	20 x 11	238
STA F 100 - 100/160 E	245 x 100 x 8	-	20 x 11	238
STA F 160-100-E	160 x 200 x 8	-	20 x 11	180

Configuration: Base plate welded to Octagon F 100 or F 80.

Material:

- Base plate: Steel, HCP;

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

- Octagon: Steel, HCP.

APPROVALS

CE mark, according to EN 1090.

CE

Codice	Nome	Peso	Numero di pezzi
113073	STA F 100	2.43	1
113337	STA F 100-80 per framo F80	1.96	1
113074	STA F 100-E	2.19	1
113481	STA F 100-80-E per framo F80	1.8	1