MIDDLE CLIP PV 1-M



APPLICATION

Middle fastening and assembly block for all typical framed Photovoltaic panels to be used with high loads caused by wind suction. Suits panel thicknesses (H) of 35 - 50 mm for any angle. Bimetal corrosion resistance, by using seal-coating on the support (washer and sleeve). Clamping forces applied at outer edge of panel to prevent undue tensioning of glass.

SCOPE OF DELIVERY

Fully assembled unit comprising Speed Nut, Support and Clip. No loose parts.

INSTALLATION

Fix Middle Clip into the required position by pressing the Speed Nut into the channel. Slide the Middle Clip along the channel so that it grips onto the existing PV panel already in position. Put the next panel on the frame and tighten the Middle Clip with max 10 Nm.

TECHNICAL DATA

Material:

- Clip: Aluminium
- Screw:Stainless steel 304
- Stud bolt, Washer and Speed Nut: HCP.

Codice	Nome	Peso	Numero di pezzi
199510	PV1-M 28-50 mm alluminio	0.1	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com