DUO CLAMP SRS SS



APPLICATION

Two-piece clamp with thread connection M8 or M10 for the installation of pipelines.

SCOPE OF DELIVERY

Supplied with two bolts particularly pre-screwed on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidential unscrewing.

TECHNICAL DATA

Size range[mm]	For pipe[NB]	Max. perm.working load [kN]	Tightening torque[Nm]	Threadconnection	MaterialW x th[mm]
13 - 18	1/4" + 3/8"	0,6	2	M8	20 x 1.5
19 - 22	1/2"	0,6	2	M8	20 x 1.5
27 - 30	3/4"	0,6	2	M8M8	20 x 1.5
32 - 36	1"	0,6	2	M8	20 x 1.5
40 - 44	1 1/4"	0,6	2	M8	20 x 1.5
48 - 54	1 1/2"	0,6	2	M8	20 x 1.5
60 - 66	2"	0,6	2	M8	20 x 1.5
68 - 73	-	0,6	2	M8	20 x 1.5
75 - 80	2 1/2"	2,5	2	M10	25 x 2.0
84 - 89	3"	2,5	2	M10	25 x 2.0
102 - 108	-	2,5	2	M10	25 x 2.0
110 - 115	4"	2,5	2	M10	25 x 2.0
129 - 140	5"	2,5	2	M10	25 x 2.5
159 - 169	6"	2,5	2	M10	25 x 2.5

The recommended load is calculated using specific statistical methods relating to break load and is designed to restrict

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

deflection to 1.5 mm or 2 % of the maximum applicable clamping diameter.

Material: Stainless steel A4 .

Codice	Nome	Peso	Numero di pezzi
170587	13 - 18 mm ¼''-3/8''	0.04	100
170602	19 - 22 mm ½''	0.05	100
170611	27 - 30 mm ¾''	0.05	100
170620	32 - 36 mm 1''	0.05	100
170639	40 - 44 mm 1 ¼''	0.06	50
170648	48 - 54 mm 1 ½''	0.07	50
170657	60 - 66 mm 2''	0.08	50
173342	68 - 73 mm	0.09	25
170666	75 - 80 mm 2 ½''	0.15	25
170675	84 - 89 mm 3''	0.16	25
173351	102 - 108 mm	0.19	25
170684	110 - 115 mm 4''	0.2	25
110882	129 - 140 mm 5''	0.26	25
110883	159 - 169 mm 6''	0.31	25