FLEXCON SOLAR 10 BAR



TECHNICAL SPECIFICATIONS

All welded construction.
Red (RAL 3002) epoxy powder coating.
Maximum working pressure: 10.0 bar.
Vessels in accordance with EN13831.
Suitable for systems with a maximum flow temperature of 120 °C.
Maximum temperature diaphragm: 110 °C.
Suitable for addition of glycol-based anti-freeze up to 50%.
In accordance with Pressure Equipment Directive 2014/68/EU.
Diaphragm: butyl rubber.
Flexcon Solar 110 - 300: including mounting kit.

Warranty 5 year.

Type	Capacity [litri]	Precharge [bar]	Ø [mm]	H [mm]	Connection (M)
Flexcon Solar 110	110	3	484	784	1"
Flexcon Solar 140	140	3	484	950	1"
Flexcon Solar 200	200	3	600	960	1"
Flexcon Solar 300	300	3	600	1330	1"
Flexcon Solar 425	425	3	790	1180	1"
Flexcon Solar 600	600	3	790	1540	1"
Flexcon Solar 800	800	3	790	1888	1"
Flexcon Solar 1000	1000	3	790	2268	1"

Codice	Nome	Peso	Numero di pezzi
16067	110 L	40	-
16068	140 L	47	8
16069	200 L	60	-

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
16070	300 L	78	-
16071	425 L	108	-
16072	600 L	138	-
16073	800 L	178	-
16074	1000 L	220.5	-