

FLEXVENT SOLAR



APPLICATION

Manually operated deaerator for solar systems with glycol based solutions. (Top version is automatic)

The water within the installation contains air which can form corrosion and reduce the thermal transfer. A Flexvent is fitted at places where the air collects. Float operated, the air is collected in the Flexvent causing the float to drop and open the air release valve. When the air is eliminated the float rises and closes the valve.

Flexvent float vents are made of brass. Most types are equipped with a shut-off valve for easy fitting and dismantling.

A Flexvent float vent is easy to fit in any installation due to its very small dimensions.

The relatively large air cushion at the top of each type of Flexvent float vent protects the valve seat sufficiently against contamination, so that the Flexvent will not leak.

To guarantee top quality, we test all Flexvents before they leave our facility!

Codice	Nome	Peso	Numero di pezzi
27785	Flexvent 3/8"	0.14	50
28505	Flexvent Top 3/8"	0.14	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com