

PRESCOR S



APPLICATION

For protection against excessive pressure in heating systems according to DIN EN 12828 with a maximum temperature not exceeding 120 ° C.

TECHNICAL DATA

Material: steel

Max working temperature: 120 °C.

Min working temperature:-10°C.

Max % glycol: 50%

INSTALLATION

Prescribed vertical installation in accordance with local regulations.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVALS

Marked TUV.

Codice	Nome	Peso	Numero di pezzi
29203	1"1/4 F × 1"1/2 F 3,0 bar	2.21	1
29211	1"1/4 F × 1"1/2 F 10,0 bar	2.28	1
29225	1"1/2 F × 2" F 4,0 bar	2.67	1
29227	1"1/2 F × 2" F 5,0 bar	2.68	1
29231	1"1/2 F × 2" F 10,0 bar	2.8	1
29245	2" F × 2"1/2 F 4,0 bar	5.74	1
29248	2" F × 2"1/2 F 6,0 bar	6.08	1
29251	2" F × 2"1/2 F 10,0 bar	6.19	1
29247	2" F × 2"1/2 F 5,0 bar	5.74	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com