

FLAMCO CLEAN SMART PN10 120° - prosystemitalia.com

FLAMCO CLEAN SMART PN10 120°



APPLICATION

Dirt separation Flamco Clean Smart with insulation EcoPlus

INSTALLATION

It can be installed either horizontally or vertically thanks to the swivel connector. The device must be placed on the return pipe, upstream of the boiler.

TECHNICAL DATA

Materials: brass and high grade plastics.

Insulation material: EPP

Thickness: 20mm

Insulation coefficient (λ): 0.036 W/mK

Max. working temperature: 120 °C.

Max. working pressure: 10 bar.

Max % glycol: 50%

Type	A [mm]	C [mm]	D [mm]	K [mm]	L [mm]	M [mm]	H1 [mm]	H2 [mm]
Flamco Clean Smart 3/4"	97	164	100	78	56	140	216	196

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	A [mm]	C [mm]	D [mm]	K [mm]	L [mm]	M [mm]	H1 [mm]	H2 [mm]
Flamco Clean Smart 22mm	97	164	120	78	56	140	216	196
Flamco Clean Smart 1"	112	189	106	91	63	178	255	241
Flamco Clean Smart 1 1/4"	112	199	110	96	63	178	255	241
Flamco Clean Smart 1 1/2"	131	224	129	109	73	212	300	285
Flamco Clean Smart 2"	131	237	140	117	73	212	300	285

Codice	Nome	Peso	Numero di pezzi
30031	3/4"	1.15	1
30032	22mm	1.25	1
30033	1"	1.56	1
30035	1"1/2	2.26	1
30036	2"	2.7	1
30034	1"1/4	1.7	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com