PROVENT JUNIOR



APPLICATION

PROflexvent float-type deaerators are suitable for closed-circuit heating or cooling systems (Prosolar suitable for solar systems). They expel air, microbubbles and other gases from the system, quickly, automatically and reliably.

MOUNTING

Deaerators must be mounted vertically at points in the circuit where air pockets tend to form. (eg change of quota).

Technical data	ProflexVent	Protop	Prosolar
Body:	Brass, nickel-plated	Brass	Brass
Connections:	threaded ½”	threaded ½”	threaded ½”
Max. operating temperature:	110 ° C	110 ° C	160 ° C
Max. operating pressure:	10 bar	10 bar	10 bar

Model	H [mm]	L [mm]	e [Inch]
ProFlexVent	102	Ø 38	1/2"
Protop	102	Ø 59	1/2"
Prosolar	102	Ø 59	1/2"

Provent junior instruction manual

Codice	Nome	Peso	Numero di pezzi
32450	Provent ½''	0.1	100

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com