AIRFIX D



APPLICATION

For use in potable water or fresh water installations.

The inside of the Airfix vessel has a special coating which prevents oxidation. The composition of the diaphragm has been made for this range in such a way that there will be no variation in smell, colour or taste. The famous Flexcon clench ring construction allows the water section to be coated before assembly.

The Airfix D is fitted with a special synthetic full flow through device which eliminates the formation of unwanted bacteria.

TECHNICAL DATA

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 8-10 bar

Pre-charge pressure: 4 bar

Type	Pre-charge[bar]	Max working pressure [bar]	ø[mm]	H [mm]	Connection
Airfix D 8	4	10	245	301	3/4"
Airfix D 12	4	10	286	334	3/4"
Airfix D 18	4	10	328	325	3/4"
Airfix D 25	4	10	358	378	3/4"
Airfix D 35	4	8	396	437	3/4"

APPROVALS

- CE 0045 in according with PED 97/23/EC

- DVGW

- Accordant to European Directive 2002/16/CE

Codice	Nome	Peso	Numero di pezzi
14259	8 L PN 10	4.1	50

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
14349	12 L PN 10	5.2	36
14459	18 L PN 10	6.2	24
14559	25 L PN 10	8.1	18
14659	35 L PN 8	9.9	18