

FLEXVENT MAX



APPLICATION

The cap of the Flexvent Max is conical in shape. The advantage of this construction is that the clearance between the water level and venting valve is maximized.

The air escape duct can be opened or closed with an adjusting screw.

The venting valve forms an integral part of the cap, so that it is impossible to damage the floatvent mechanism from outside.

The relatively large air cushion at the top of each type of Flexvent float vent protects the valve seat sufficiently against contamination, so that the Flexvent will not leak.

TECHNICAL DATA

Material: brass

Min./max. operating temperature: - 10 °C / 120 °C.

Min./max. operating pressure: 0.2 / 25.0 bar.

Suitable for water and water/glycol solutions up to 50% glycol.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
28550	Max 3/4"	1	10

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com