

PRESCOR SOLAR



APPLICATION

For Flamcovent and Flexair.

The venting duct can be opened or closed with an adjustable screw. The ventilation valve forms a whole with the cap, so that it is impossible to damage the mechanism from the outside.

TECHNICAL DATA

Material: brass

Max working pressure: 10 bar

Max working temperature: 120 °C.

Min working temperature: -10°C.

Codice	Nome	Peso	Numero di pezzi
--------	------	------	-----------------

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
28310	1/2" × 3/4" 3,0 bar	0.18	-
28311	1/2" × 3/4" 6,0 bar	0.16	-
28316	3/4" × 1" 6,0 bar	0.22	-
28317	3/4" × 1" 8,0 bar	0.22	-
28321	1" × 1 1/4" 6,0 bar	0.47	-
28322	1" × 1 1/4" 8,0 bar	0.47	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com