


## FLEXCON TOP



### TECHNICAL DATA

Max. operating pressure: 6.0 bar.  
 Vessels in accordance with EN13831.  
 Suitable for systems with a maximum flow temperature of 120 °C.  
 Max. temperature diaphragm: 90 °C.  
 Deep drawn zinc plated steel clench ring.  
 Suitable for addition of glycol-based anti-freeze up to 50%.  
 Red (RAL 3002) epoxy powder coating.  
 In accordance with Pressure Equipment Directive 2014/68/EU.

Type [L]	Precharge [bar]	A [mm]	B [mm]	Ø C [mm]	D [mm]	E
2	2,5	216	144	-	-	R 3/4"
4	2,5	216	194	-	-	R 3/4"
8	2,5	245	280	-	-	R 3/4"
12	2,5	286	313	-	-	R 3/4"
18	2,5	328	306	-	-	R 3/4"
25	2,5	358	359	-	-	R 3/4"
35	2,5	396	435	263	117	R 3/4"
50	2,5	437	492	263	132	R 3/4"
80	2,5	519	540	360	142	R 1"

Codice	Nome	Peso	Numero di pezzi
13203	Flexcon Top da 6 bar	2.1	-

#### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
 30030 Pianiga - Venezia - Italy  
 T +39.041.510.1622  
 F +39.041.5131351

P.IVA 03470750278  
 Reg.Imp. Ve 03470750278  
 Cap.soc. € 90.000,00  
 REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)