FLEXCON TOP



TECHNICAL DATA

Max. operating pressure: 6.0 bar.
Vessels in accordance with EN13831.
Suitable for systems with a maximum flow temperature of 120 °C.
Max. temperature diaphragm: 90 °C.
Deep drawn zinc plated steel clench ring.
Suitable for addition of glycol-based anti-freeze up to 50%.
Red (RAL 3002) epoxy powder coating.
In accordance with Pressure Equipment Directive 2014/68/EU.

Type [L]	Precharge [bar]	A [mm]	B [mm]	Ø C [mm]	D [mm]	E
2	2,5	216	144	-	-	R 3/4"
4	2,5	216	194	-	-	R 3/4"
8	2,5	245	280	-	-	R 3/4"
12	2,5	286	313	-	-	R 3/4"
18	2,5	328	306	-	-	R 3/4"
25	2,5	358	359	-	-	R 3/4"
35	2,5	396	435	263	117	R 3/4"
50	2,5	437	492	263	132	R 3/4"
80	2,5	519	540	360	142	R 1"

Codice	Nome	Peso	Numero di pezzi
13203	Flexcon Top da 6 bar	2.1	-

PROSYSTEM ITALIA SRL
Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com