

FLEXCON M-K/C PN6 - prosystemitalia.com

FLEXCON M-K/C PN6



APPLICATION

For smaller heating and chilled water (cooling) installations.

This product is especially designed for smaller commercial systems with limited space, providing all the benefits of an automat.

TECHNICAL DATA

Material: steel, Red (RAL 3002)

Operating pressure: 5,2 bar (PN6)

Min. working temperature: -10.0°C

Max working temperature: 70°C

Max working temperature at outlet: 120 °C.

Max % glycol: 50%

APPROVALS

CE 0045 in according with PED 97/23/EC.

Type	Capacity [litri]	Ø [mm]	H [mm]	Connection (F)
Flexcon M-K/C 110	110	509	1215	G1"
Flexcon M-K/C 200	200	600	1391	G1"

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	Capacity [litri]	Ø [mm]	H [mm]	Connection (F)
Flexcon M-K/C 350	350	790	1459	G1"
Flexcon M-K/C 425	425	790	1612	G1"

Codice	Nome	Peso	Numero di pezzi
23225	110 L	37	-
23227	350 L	81	-
23228	425 L	91	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com